

17' GEN 2 PUP (SPRING RIDE)

52873(WHITE) 52873(SILVER) SL1700-G2

Capacity: 16 yd/3 TARE: 11800 lbs

GENERAL SPECIFICATIONS

Dimensions: Box Length 17', Outside Width 8', Overall Length 30'4", Overall Height 112", Wall Height 46"

Landing Gear: 1 Jack 7000lb Extendable Landing Gear

Pintle Eye: Holland DB1407-SE Forged 2.38" ID Drawbar

Frame: 10" @ 26 WF Beam

Box: Single Wall & Floor Gen 2 Tub 4mm Hardox 450, 4mm Hardox 450 Supports, Tub Designed For Maximum Strength, Weight, and Cleanout

Fenders: Minimizer Polyethylene Fenders

Cylinder: 35 Ton 4 Stage -5.5" Base x 157" Stroke, 1" Male Quick Coupler at Front of Trailer

Ladders: Ladder at back on D/S

Gate: Formed 3/16" Hardox 450 plate

Boards: 12" Painted Side Boards, 6 plank brackets

Air System: Standard Air Tanks

Tires: Dunlop SP832 On/Off Road

Rims: 24.5" x 8.25" Polished Aluminum 10 Bolt (inner & outer)

Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards

Suspension: IMT Spring Ride with Three 23,000lb Axles @ 98" Spread, 17" Ride Height, 77 1/2" Track Width, Stemco Wheel Seals, EP2 Lithium Greased Hub System

Brakes: 16.5" x 7" Extended Life Antilock Braking System, Bendix TABS-6 ABS (2 Sensors/1 Modulator), Meritor Auto Slack Adjusters, Spring Brake Pots 30/30 TSE, 23.75" Cam Length – IMT Wheel End Cast Hub and Drum

STANDARD FEATURES

Coating Frame: Complete Steel
Shot Blasted, PPG DTM
Urethane

Coating Box: Epoxy Primer
Inside and Out, Top Coat PPG
Urethane, All Painted Parts
Baked in Heat Ovens

Painted Side Boards: Black

Colors: White or Silver (custom
colors available – see options)

Board Gussets: 3 Per Side

Bumpers: Rear Light Bar

Document Holder: Included

Safety: Reflective Tape

Lighting: Phillips HD Sealed Wiring Harness System, Rubber Mounted LED as per CMVSS with Side Signals

Tarp: 22 oz Electric Black Mesh flip tarp c/w lower Manual Backup Bracket

Mudflaps: RENN Mudflaps at Rear of Axles

