

17' PUP (AIR RIDE)

64802(WHITE) 69362(SILVER) SL1700

Capacity: 15.76 yd/3 TARE: 12960 lbs

GENERAL SPECIFICATIONS

Dimensions: Box Length 17', Outside Width 8', Overall Length 30'4", Overall Height 82-15/16", Wall Height 30", Tip Height 210"

Landing Gear: 1 Jack 7000lb Extendable Landing Gear

Pintle Eye: Holland DB1407-SE Forged 2.38" ID Drawbar

Frame: 10" @ 26 WF Beam

Box: Double Wall with 12 Gauge AR200 Plate Inner Walls, 12 Gauge Formed HTS Outer Walls, Floor 3/16" AR200 formed up each side, 42" Flat Front 3/16" AR200, Full Length 12 Gauge Fender Skirts

Cylinder: 35 Ton 4 Stage -5.5" Base x 156" Stroke, 1" Male Quick Coupler at Front of Trailer

Ladders: Ladder at back on D/S

Gate: Inner 3/16" AR200 plate, Outer 12 Gauge HTS, Formed Cross Ribs, Straight Gate w/Air Trip

Boards: 12" Painted Side Boards, 6 plank brackets

Air System: Standard Air Tanks

Tires: Cooper RoadMaster 230 HH On/Off Road

Rims: 24.5" x 8.25" Steel Powder-coated (inner & outer)

Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards

Suspension: SAF Holland Air Ride with Three 23,000lb axles @ 98" Axle Spread, 17" Ride Height, 77 1/2" Track Width, Wheel Seals Stemco Guardian HP

Brakes: 16.5" x 7" Extended Life Antilock Braking System, Bendix TABS-6 ABS (2 Sensors/1 Modulator), Meritor Auto Slack Adjusters, Spring Brake Pots 30/30 TSE, 23" Cam Length – SAF Holland Wheel End Cast Hub and Drum

STANDARD FEATURES

Coating Frame: Complete Steel
 Shot Blasted, PPG DTM
 Urethane

Coating Box: Epoxy Primer
 Inside and Out, Top Coat PPG
 Urethane, All Painted Parts
 Baked in Heat Ovens

Painted Side Boards: Black

Colors: White or Silver (custom colors available – see options)

Bumpers: Rear Light Bar

Document Holder: Included

Safety: Reflective Tape

Lighting: HD Sealed Wiring Harness System, Rubber Mounted LED as per CMVSS with Side Signals

Tarp: 22 oz Electric Black Mesh flip tarp c/w lower Manual Backup Bracket

Mudflaps: RENN Mudflaps at Front & Rear of Axles

